

CKC

LIGHT IT LIKE IT



Followw



Adopts 1800W CW LED dual-display light source
 Total luminous flux 61,000 lumens (High Brightness mode) / 40,000 lumens (High CRI mode)
 Beam Angle 3.5° ~18° zoom
 CCT 6500K
 Switchable Ra:95 / R9:95

OPTAL

- Source: 1800W CW LED (High CRI + High Output)
- Output: 61000 Lm(High Brightness) / 40000 Lm(High CRI)
- Beam angle: 3.5 ~ 18°
- CCT: 6500K
- CRI:Ra-71 (High Brightness)
Ra-95/ R9-95(High CRI)
- Lens diameter: 230 mm
- Source lifetime: >20000 H

EFFECT

- Strobe: 1 ~ 25Hz
- LED Refresh Frequency: 900Hz~ 25KHz
- Plug in Electronic Rotating Gobo
- Electronic Color wheel (Open/Red/Blue/Green/Orange/Fuchsia)
- Electronic CCT wheel (3000K/4000K/5600K/6500K/8500K)
- Fast switching between high CRI and high brightness
- Manual Iris
- Electronic dimming/Manual dimming
- Dimmer curve: 4
- Frost: Light frost + Heavy frost

CONTROL & PROGRAM

- Channel: 1CH/2CH/7CH/8CH
- Protocol: DMX512, RDM
- Data connector: 3 PIN XLR (Optional 5 PIN XLR)
- Display: 2.8 inches touch screen
- NFC: The lighting fixtures do not require power on and can be directly set up, diagnosed, and perform other functions through the CKC app
- Overload protector

SOFTWARE

- Via USB & DMX signal to update
- Silent fan, intelligent speed regulation
- Intelligent temperature protection to ensure LED service life

HOUSING

- Aluminum alloy structure
- Fan cooling(intelligent speed regulation)

PAN & TILT MOVEMENT

- Pan: Manual 360°
- Tilt: Manual ±35°

POWER CONSUMPTION


- Voltage: AC 100V ~ 240V 50/60Hz
- Rated power: 2380 W

OTHER

- IP rating: IP30
- Work environment: -40°C ~ 45°C
- Startup environment: -20°C ~ 45°C

SIZE & WEIGHT

- Size: 511 × 1024 × 576 mm
- N.W: 46.6 kgs




PHOTOMETRICAL DATA

Distance(m)	0	8	15	30	50	100
Lux 3.5°						
CRI:71		103000	29200	7324	2637	895
CRI:95		65300	18500	4644	1672	576
Diameter(m)		0.49	0.92	1.83	3.06	6.11
Lux 18°						
CRI:71		12900	3669	917	330	144
CRI:95		8190	2330	582	210	90
Diameter(m)		2.53	4.75	9.50	15.84	31.68

Accessories



Color gel frame holder
 Six color filters can be placed at the same time



Reflex sight



Pulley Tripod Stand

✂ 642 mm ✂ 992 mm
 ⚖ 20.1 kgs ⚖ 958 mm



Conventional Tripod Stand

✂ 780 mm ✂ 1023 mm
 ⚖ 890 mm ⚖ 10.7 kgs
 ⚖ 1312 mm